

Nominal OD	Dimensions			Details		Properties	
	Actual Sizes			SCH. NO.	Wall Type (STD., XHY., XXHY)	Weight per linear foot lbs	Section Modulus In. ³
	OD In./cm	Wall In./cm	ID In./cm				
6	6.625	0.250	6.125	-	-	17.040	7.691
		0.280	6.065	SCH. 40	STD	18.994	8.496
		0.312	6.001	-	-	21.059	9.342
		0.344	5.937	-	-	23.101	10.111
		0.375	5.875	-	-	25.058	10.893
		0.432	5.761	SCH. 80	XHY	28.604	12.224
		0.500	5.625	-	-	32.743	13.711
		0.562	5.501	SCH. 120	-	36.430	14.981
		0.625	5.375	-	-	40.093	16.182
		0.250	8.125	SCH. 20	-	22.385	13.385
8	8.625	0.277	8.071	SCH. 30	-	24.723	14.690
		0.312	8.001	-	-	27.730	16.368
		0.322	7.981	SCH. 40	STD	28.584	16.809
		0.344	7.937	-	-	30.456	17.808
		0.375	7.875	-	-	33.077	19.214
		0.406	7.813	SCH. 60	-	35.677	20.587
		0.438	7.749	-	-	38.339	21.928
		0.500	7.625	SCH. 80	XHY	43.434	24.514
		0.562	7.501	-	-	48.447	26.963
		0.594	7.437	SCH. 100	-	51.003	28.177
10	10.750	0.625	7.375	-	-	53.457	29.324
		0.250	10.250	SCH. 20	-	28.065	21.156
		0.279	10.192	-	-	31.234	23.418
		0.307	10.136	SCH. 30	-	34.277	25.566
		0.344	10.062	-	-	38.272	28.332
		0.365	10.020	SCH. 40	STD	40.526	29.904
		0.375	10.000	-	-	41.596	30.637
		0.438	9.874	-	-	48.290	35.118
		0.500	9.750	SCH. 60	XHY	54.794	39.433
		0.562	9.626	-	-	61.216	43.584
12	12.750	0.594	9.562	SCH. 80	-	64.498	45.628
		0.625	9.500	-	-	67.657	47.577
		0.250	12.250	SCH. 20	-	33.411	30.090
		0.281	12.188	-	-	37.461	33.602
		0.312	12.126	-	-	41.490	37.060
		0.330	12.090	SCH. 30	-	43.820	38.973
		0.344	12.062	-	-	45.628	40.465
		0.375	12.000	-	STD	49.615	43.817
		0.406	11.938	SCH. 40	-	53.582	47.104
		0.438	11.874	-	-	57.655	50.367
14	14.000	0.500	11.750	-	XHY	65.485	56.713
		0.562	11.626	SCH. 60	-	73.233	62.828
		0.625	11.500	-	-	81.021	68.811
		0.688	11.374	SCH. 80	-	88.725	74.636
		0.250	13.500	SCH. 10	-	36.752	36.471
		0.281	13.438	-	-	41.216	40.755
		0.312	13.376	SCH. 20	-	45.660	44.979
		0.344	13.312	-	-	50.225	49.144
		0.375	13.250	SCH. 30	STD	54.627	53.251
		0.406	13.188	-	-	59.008	57.301
16	16.000	0.438	13.124	SCH. 40	-	63.509	61.356
		0.459	13.082	-	-	66.451	64.023
		0.500	13.000	-	XHY	72.167	69.108
		0.562	12.876	-	-	80.744	76.701
		0.594	12.812	SCH. 60	-	85.138	80.466
		0.625	12.750	-	-	89.374	84.076
		0.688	12.624	-	-	97.919	91.317
		0.250	15.500	SCH. 10	-	42.098	47.958
		0.281	15.438	-	-	47.225	53.636
		0.312	15.376	SCH. 20	-	52.331	59.245
18	18.000	0.344	15.312	-	-	57.581	64.787
		0.375	15.250	SCH. 30	STD	62.645	70.261
		0.406	15.188	-	-	67.689	75.668
		0.438	15.124	-	-	72.875	81.008
		0.469	15.062	-	-	77.877	86.283
		0.500	15.000	SCH. 40	XHY	82.859	91.493
		0.562	14.876	-	-	92.761	101.720
		0.625	14.750	-	-	102.738	111.690

Nominal OD	Dimensions			Details		Properties	
	Actual Sizes			SCH. NO.	Wall Type (STD., XHY., XXHY)	Weight per linear foot lbs	Section Modulus In. ³
	OD In./cm	Wall In./cm	ID In./cm				
18	18.000	0.250	17.500	-	-	47.443	61.015
		0.281	17.438	-	-	53.233	68.284
		0.312	17.376	SCH. 20	-	59.003	75.475
		0.344	17.312	-	-	64.936	82.589
		0.375	17.250	-	STD	70.664	89.626
		0.406	17.188	-	-	76.371	96.587
		0.438	17.124	SCH. 30	-	82.240	103.470
		0.469	17.062	-	-	87.906	110.280
		0.500	17.000	-	XHY	93.550	117.020
		0.562	16.876	SCH. 40	-	104.778	130.270
20	20.000	0.625	16.750	-	-	116.103	143.230
		0.688	16.624	SCH. 60	-	127.342	156.044
		0.750	16.500	-	-	138.321	168.290
		0.281	19.438	-	-	59.242	84.699
		0.312	19.376	-	-	65.674	93.668
		0.344	19.312	-	-	72.292	102.550
		0.375	19.250	SCH. 20	STD	78.683	111.350
		0.406	19.188	-	-	85.052	119.710
		0.438	19.124	-	-	91.606	128.690
		0.469	19.062	-	-	97.934	137.230
22	22.000	0.500	19.000	SCH. 30	XHY	104.242	145.690
		0.562	18.876	-	-	116.795	162.360
		0.594	18.812	SCH. 40	-	123.242	170.670
		0.625	18.750	-	-	129.467	178.700
		0.688	18.624	-	-	142.054	194.890
		0.312	21.376	-	-	72.345	113.820
		0.344	21.312	-	-	79.648	124.670
		0.375	21.250	SCH. 20	STD	86.701	135.420
		0.406	21.188	-	-	93.734	146.080
		0.438	21.124	-	-	100.972	156.650
24	24.000	0.469	21.062	-	-	107.963	167.120
		0.500	21.000	SCH. 30	XHY	114.933	177.500
		0.562	20.876	-	-	128.812	197.980
		0.625	20.750	-	-	142.831	218.080
		0.688	20.624	-	-	156.765	238.060
		0.312	23.376	-	-	79.017	135.771
		0.344	23.312	-	-	87.004	149.096
		0.375	23.250	SCH. 20	STD	94.720	161.899
		0.406	23.188	-	-	102.415	174.603
		0.438	23.124	-	-	110.338	187.609
26	26.000	0.469	23.062	-	-	117.991	200.104
		0.500	23.000	-	XHY	125.625	212.501
		0.562	22.876	SCH. 30	-	140.830	236.995
		0.625	22.750	-	-	156.196	261.477
		0.688	22.624	SCH. 40	-	171.477	285.560
		0.312	25.376	SCH. 10	-	85.688	159.823
		0.344	25.312	-	-	94.359	175.563
		0.375	25.250	-	STD	102.738	190.696
		0.406	25.188	-	-	111.097	205.721
		0.438	25.124	-	-	119.703	221.114
28	28.000	0.469	25.062	-	-	128.020	235.912
		0.500	25.000	SCH. 20	XHY	136.316	250.603
		0.562	24.876	-	-	152.847	279.658
		0.625	24.750	-	-	169.560	308.737
		0.656	24.688	-	-	177.753	322.886
		0.688	24.624	-	-	186.188	337.379
		0.344	27.312	-	-	101.715	204.192
		0.375	27.250	-	STD	110.757	221.650
		0.406	27.188	-	-	119.778	239.392
		0.438	27.124	-	-	129.069	257.372
30	30.000	0.469	27.062	-	-	138.049	274.668
		0.500	27.000	SCH. 20	XHY	147.008	291.847
		0.531	26.938	-	-	155.946	308.907
		0.562	26.876	-	-	164.864	325.852
		0.594	26.812	-	-	174.048	343.219
		0.625	26.750	SCH. 30	-	182.824	359.924
		0.656	26.688	-	-	191.780	376.517
		0.688	26.624	-	-	200.900	393.522